



Moldex DECK!TM Protector

Composite deck mildew proof sealer and color rejuvenator

Description

Moldex DECK!TM Protector is a water-based, self-crosslinking acrylic, sealer designed specifically for composite decking. This finish is designed to seal the composite material, unlike solid deck stains, paint, and high-build coatings that are often prone to peeling, cracking, or chipping. This chemistry is formulated using nano-particles to penetrate the surface of the composite material while coating the exposed cellulose or wood fibers exposed on the surface. When applied properly, a single coat of clear will seal your deck without leaving a shiny appearance. Additional coats may be applied to deepen the natural color and create a wet look. Restoring the colored appearance of your composite deck is easy with a choice of Cedar Tone, Mahogany, and Coastal Gray. Moldex DECK! Protector guarantees a mold, mildew and algae resistant finish for 4 years when used with Moldex DECK! Cleaner Concentrate.

Coverage:

Expect coverage of 400 square feet per gallon on composite materials. Expect 200 to 300 square feet per gallon on new wood and 150 to 200 square feet per gallon on older wood. Apply as much as wood will absorb for longest lasting, most beautiful protection.

Surface Preparation:

Surface must be sound free from any dirt, or loose foreign materials, oil, grease, and standing water. Remove all existing mold & mildew stains prior to use using Moldex DECK! Cleaner Concentrate. Allow surface to dry completely. Moldex Deck! is self-priming however, if your intended application differs from those specified, test a small area first.

Application:

Shake container thoroughly. Always test a small, hidden area for desired finish and adhesion. Empty contents into a garden-type sprayer. If using multiple gallons, mix together for color consistency. Spray liberally onto the surface. When using a sprayer, immediately back-brush using a synthetic brush, roller, or stain pad. Apply the product evenly and work in to promote penetration and minimize puddling. Apply with the grain completing a full board or set of boards so as not to overlap. Re-disperse excess coating. Do not apply to frozen wood, in direct sunlight or if rain is imminent. Allow 24 hours of dry time before foot traffic. After sealing, deck should be free from rain or standing water for 24 hours to avoid water spotting. Only one coat is necessary for a natural finish. Apply two coats to rejuvenate color of faded composite. Additional coats of clear will create a "wet look" finish while, additional coats of colors will create a deeper colored finish. Allow first coat to dry to the touch before applying additional

coats. Always test a small area for desired finish. Best when applied to clean, dry surface. Do not over-apply.

IMPORTANT: DO NOT MIX Moldex DECK!TM Protector with other materials or dilute.

Clean up:

Clean brushes and equipment with warm water and detergent. Dispose of any cans or unused portions of material according to local, state and federal regulations. Close container when not in use.

Limitations:

It is possible that this product has not been tested for all types of composite materials. Test a small area for adhesion and desired performance prior to application to the entire surface.

Do not use Moldex DECK!TM Protector indoors.

Storage:

Shelf life: 2 years @ 75°F (24°C)

Store indoors: 40°F - 80°F (4°C -27°C)

Freeze / thaw stable

Warranty:

When applied to recommended surfaces and as directed according to the instructions on the label, this product will perform as claimed. The coating film is guaranteed to resist mildew growth for up to 48 months. The contents of the container are warranted for a period of 2 years when stored properly. If the contents of the container are proven to be defective, EnviroCare will refund at the full purchase price or replace the product at the company's option. This warranty does not include labor or cost of labor for application or damages related to the use or misuse of this product. This warranty gives you specific rights and you may also have other rights that vary from state to state.

Personal Safety, First Aid, and Storage and Handling

See the Material Safety Data Sheet (MSDS) for product specific information.

Technical Assistance

For help in selecting or evaluating these products for your application, please call the Technical Service experts at: 1-877-463-2628.

Ordering Information – Product or Literature

To order ForsiteTM or additional literature, call Customer Service at 1-877-463-2628 or the local



EnviroCare Corporation

260 Fordham Road
Wilmington, MA 01887
Phone: (978) 658-0123
Fax: (978) 964-0444
www.envirocarecorp.com